

GTE 80

FOR SMALL GAS TURBINES UP TO 14 MW

EQUIPMENT DESCRIPTION

THE GTE 80 is designed for stationary gas turbines. GTE 80 can be fitted with a wheel kit for mobility on flat concrete type surfaces. An integrated control panel enables easy user operation. This unit is available EEXD Zone-1 classed for hazardous area applications. GTE 80 is available with two 40 litre tanks, one for washing fluid and one for rinse water.

All GTE equipment is designed for customer installation. Instructions and necessary information are included in the Owner's Manuals. On-line and off-line wash is performed with the same nozzles, pressure and flowrate (GTE nozzle design).



STANDARD FEATURES

- Stainless steel tank with visual level
- Stainless steel chassis or powder coated on zinc primer chassis
- Operator panel
- Connectors - Parker or customer specific
- In tank heater with low level shut-off
- Individual thermostat with indicator for each tank
- Adjustable pressure relief valve for outlet pressure
- Pressure gauge
- Automatic out of fluid shut-off
- Filter on pump's suction side
- Emergency stop button
- Electrical main switch
- Documentation set includes Owner's manual, test reports (hydrostatic, leak and functional)
- Certificate of Conformity

OPTIONAL FEATURES

- Stainless steel chassis
- Flexible, custom length high pressure hose
- In unit, halogen free wiring
- Tropical protected electrical motor
- Tropical protected tank 1/tank 2 electrical valve actuators
- Stainless steel electrical boxes
- Frost guard

TECHNICAL DATA

Length 870 mm (34 inch)	Tank Capacity 2 x 40 litre (2 x 10.6 gal)
Width 510 mm (20 inch)	Standard Power Supply 3ph, 380-420V, 50Hz, Fuse 16 Amp
Height 1150 mm (45 inch)	or 3ph, 440-480V, 60Hz Fuse 16 Amp
Weight (empty) 160 kg (360 lb)	

Effective 2007-06-18. Data is subject to change without notice.